5

6

7

- 12 transporting vehicles and load with the two-foot load tolerance shall not exceed forty-seven (47) feet, and that only four (4) automobiles 13 may be transported in any single unit which transported only four (4) automobiles per unit prior to January 3, 1955.". 14 15
 - SEC. 2. The state highway commission may issue annual permits to a retail farm implement dealer to transport, on his own regular 3 delivery vehicle, farm machines from his nearest branch house or distribution point to the retailer's place of business and from the retail dealer to the customer's farm within the county of the retailer's 4 5 place of business or counties adjoining the retail dealer's place of business and shall determine and fix a tolerance of width and length 7 8 on the load carried.
 - 1 This Act being deemed of immediate importance shall be in force and effect immediately upon its passage and publication in the Reinbeck Courier, a newspaper published at Reinbeck, Iowa, 3 and in the Brooklyn Chronicle, a newspaper published at Brooklyn, Iowa.

Approved April 27, 1955.

I hereby certify that the foregoing Act, House File 445, was published in the Reinbeck Courier, Reinbeck, Iowa, May 5, 1955, and in the Brooklyn Chronicle, Brooklyn, Iowa, May 5, 1955. MELVIN D. SYNHORST, Secretary of State.

CHAPTER 169

MOTOR VEHICLE DEALERS' LICENSES

H. F. 479

AN ACT to amend chapter three hundred twenty-two (322), Code 1954, relating to the revocation of motor vehicle dealer licenses.

Be It Enacted by the General Assembly of the State of Iowa:

SECTION 1. Section three hundred twenty-two point nine (322.9), 2 Code 1954, is hereby amended by striking subsections one (1), two (2) and three (3) and substituting in lieu thereof the following: "Failing upon the sale or transfer of a vehicle to deliver to the 3 4

purchaser or transferee of the vehicle sold or transferred, a manufacturer's or importer's certificate, or a certificate of title duly assigned, as provided in chapter 321 of the Code.

8 'Failing upon the purchasing or otherwise acquiring of a vehicle 9 to obtain a manufacturer's or importer's certificate, or a certificate 10 of title duly assigned as provided in chapter 321 of the Code.

"Failing upon the purchasing or otherwise acquiring of a vehicle 11 to obtain a new certificate of title to such vehicle when and where 12 required in chapter 321 of the Code. 13

14 'Failing to mail or deliver to the treasurer of the county of such licensee's residence two copies of the signed purchase receipt within 15 forty-eight (48) hours after purchase or acquisition of a vehicle reg-16

- istered in this state as provided in section three hundred twenty-one 17 18 point forty-eight (321.48) of the Code."
 - SEC. 2. Section three hundred twenty-two point sixteen (322.16), Code 1954, is hereby repealed.

Approved April 19, 1955.

4

5

6

7

8

13 14

15

16 17

18

19

20

21

22

23

24

30 31

CHAPTER 170

MOTOR VEHICLE FUEL SPECIFICATIONS

S. F. 142

AN ACT relating to motor vehicle fuel specifications so as to bring them in line with federal specifications and to amend various sections of the Code relating thereto.

Be It Enacted by the General Assembly of the State of Iowa:

SECTION 1. Section three hundred twenty-three point two (323.2), Code 1954, is hereby repealed and the following inserted in lieu 3 thereof:

"Test and standards. Any motor vehicle fuel known or sold as motor gasoline or sold or offered for sale as a substitute for or as having the properties of motor gasoline shall conform to the following tests and specifications:

Gasoline shall be free from water and suspended matter.

9 Corrosion test. A. S. T. M. D-130 latest revision. A clean, freshly polished copper strip shall not be darker than A. S. T. M. Standard 1 10 when submerged in the gasoline for three hours at one hundred 11 twenty-two degrees (122°F.) 12

Distillation range. A. S. T. M. D-86 latest revision. When ten percent (10%) is evaporated, the thermometer shall not read more than one hundred sixty-seven degrees (167° F.).

When fifty percent (50%) is evaporated the thermometer shall not read more than two hundred eighty-four degrees (284° F.).

When ninety percent (90%) is evaporated the thermometer shall not read more than three hundred ninety-two degrees (392° F.).

The end point shall not be more than four hundred thirty-seven degrees (437° F.).

At least ninety-five percent (95%) shall be recovered as distillate in the receiver from distillation.

Residue on distillation shall not be more than two percent (2%). Sulfur A. S. T. M. D-90 latest revision.

25 26 The sulfur shall not exceed zero point twenty-five percent (0.25%). 27

Vapor pressure. A. S. T. M.-D-323 latest revision.

28 The vapor pressure at one hundred degrees (100° F.) shall not be 29 more than;

Fifteen (15) pounds per square inch during the months of November, December, January and February.

32 Twelve (12) pounds per square inch during the months of March 33 April, May, September and October.

34 Ten (10) pounds per square inch during the months of June, July 35 and August.