

567—122.13(455B,455D) Design requirements for CRT recycling facilities. A CRT recycling facility shall be designed and constructed to meet the following requirements:

122.13(1) CRT recycling facilities shall be enclosed by walls, a roof, and a floor satisfactory to:

- a.* Prevent litter from exiting the building.
- b.* Keep precipitation out of the building.

122.13(2) A CRT recycling facility shall maintain a separation between stormwater and liquids generated inside the building.

122.13(3) Discarded CRTs shall be demanufactured and processed in an area where hazardous materials can be contained.

122.13(4) A sign shall be posted at the primary entrance to the facility. The sign shall be a minimum of $8\frac{1}{2} \times 11$ inches and visible from the outside of the building at approximately eye level. The lettering shall be a minimum of 1-inch high and state the following information:

- a.* Name and permit number of facility.
- b.* Telephone number of emergency contact person(s).

122.13(5) A CRT recycling facility may store discarded CRTs and materials derived from discarded CRTs outdoors if the following conditions are met:

- a.* The facility has a stormwater permit, if applicable.
- b.* The material is not harboring or attracting vectors.
- c.* Litter is contained within the storage area or unit.
- d.* The discarded CRTs and materials derived from discarded CRTs are not broken CRTs or CRT glass.