## Senate Study Bill 2063

## **Bill Text**

PAG LIN

```
Section 1. Section 100.39, unnumbered paragraph 1, Code
   1 1
  1 2 1997, is amended to read as follows:
  1
    3 All buildings
 that are

    approved for construction

– after
 1 4
 August 15, 1975
- July 1, 1998, that exceed four stories in
 1 5 height, or
 <del>-sixty-five</del>
- <u>seventy-five</u> feet above grade, shall
  1 6 require the installation of an approved automatic fire
  1 7 extinguishing system designed and installed in conformity with
  1 8 rules promulgated by the state fire marshal pursuant to this
  1 9 chapter.
  1 10
         Sec. 2. Section <u>101.2</u>, Code 1997, is amended by striking
  1 11 the section and inserting in lieu thereof the following:
 1 12
         101.2 SCOPE OF RULES.
          Except as otherwise provided in this chapter, the rules
 1 13
 1 14 shall be in substantial compliance with the standards of the
  1 15 national fire protection association relating to flammable
  1 16 liquids and liquefied petroleum gases.
 1 17
         Sec. 3. Section 101.12, Code 1997, is amended to read as
 1 18 follows:
 1 19
       101.12 ABOVEGROUND PETROLEUM TANKS AUTHORIZED.
         Rules of the state fire marshal
  1 20
 shall permit
- permitting
  1 21 installation of aboveground petroleum storage tanks for retail
  1 22 motor vehicle fuel outlets
 as permitted by the latest edition
 1 23
 of the
- shall be in substantial compliance with the applicable
  1 24 standards of the national fire protection association
 rule
 1 25
<u> 30A</u>
-, and shall be subject to the approval of the governing
 1 26 body of the local governmental subdivision with jurisdiction
 1 27 over the site of the outlet.
          Sec. 4. Section 100.32, Code 1997, is repealed.
 1 28
  1 29
                                 EXPLANATION
```

1 30 This bill repeals Code section 100.32 that prevents the 1 31 fire marshal from providing fire safety information and 1 32 education materials when moneys are not appropriated for that 1 33 purpose, increases the new building construction height levels 1 34 at which automatic fire extinguishing systems must be 1 35 installed from 65 feet to 75 feet, and requires that the state 2 1 fire marshal's administrative rules be in substantial
2 2 compliance with the standards of the national fire protection 2 3 association relating to aboveground petroleum storage tanks,
2 4 flammable liquids, and liquefied petroleum gases.
2 5 LSB 3086DP 77
2 6 kh/sc/14