

875—63.3 (88A) Site requirements.

63.3(1) *Storage.* Adequate storage shall be provided to protect equipment from physical, chemical and ultraviolet-ray damage. The storage area shall be secured against unauthorized entry.

63.3(2) *Communications.*

- a.* There shall be a public address system in operation during the hours of business.
- b.* A radio communication link shall be established between the platform and the staff responsible for jumper registration, landing, and recovery.
- c.* There shall be a means on site to communicate with local emergency responders.
- d.* A clearly visible sign shall be placed at the entrance to the operating site setting forth medical restrictions for jumpers, the minimum-age requirement of 18 years of age, and instructions for jumpers.

63.3(3) *Wind meter.* An anemometer shall be installed in accordance with the manufacturer's recommendations and in a location easily visible to the staff.

63.3(4) *Lighting.* Adequate lighting shall be provided at a site that operates at any time during the period of one-half hour prior to sunset until one-half hour after sunrise. At a minimum, the lighting system shall be capable of lighting the jump platform, the jump space and the landing area.

63.3(5) *Fences.* The operator shall use fences in compliance with ASTM 2291-14, Part 14, to limit access to the site.

[ARC 2428C, IAB 3/2/16, effective 4/6/16; see Delay note at end of chapter]